

# Fibre Optic Dome Enclosure Upto 144 Fibres

## Description

The dome enclosure is suitable for protecting fibre cable splices in branching applications. Its well-engineered, injection-moulded outer body makes it impenetrable to the elements. It can protect splices and ensure reliability with usage in ambient temperatures from -40°C to +65 °C. It can be placed in aerial, wall mounted, or duct mounted locations.

## Features

- ▶ Holds up to 144 fibres
- ▶ Easy to re-enter
- ▶ Cable entry/exit, 1 oval and 4 round
- ▶ Integrated pressure valve
- ▶ Termination and splice kit included
- ▶ Integrated seal, airtight and waterproof
- ▶ Ideal for cable repair
- ▶ RoHS compliant
- ▶ Can be used in through, branch or mid-span splice locations
- ▶ Suitable for aerial, underground duct or direct burial applications.

## Technical Specification

Specification:		
<b>Width:</b> 223 mm	<b>Depth:</b> 450 mm	<b>Weight:</b> 2.26 kgs
Cable entry/exit, 1 oval and 4 round.		



## Ordering Information

Description	Part NO.
48 Splice dome enclosure	<b>DOME01</b>
72 Splice dome enclosure	<b>DOME02</b>
96 Splice dome enclosure	<b>DOME03</b>
144 Splice dome enclosure	<b>DOME04</b>

